













Classification		24 Hours Timer		Timer	Weekly Programmable Timer
Model		EKTM-181H	EKTM-180A	EKTM-E8	EKTM-20A
Appearance					
Contact Capacity		AC250V 16A	AC250V 16A	AC250V 16A	AC250V 20A
Full Timing Range		24h	24h	7m	Per week or per day cycle
Contact resistance		$\leq 50\text{m}\Omega$	$\leq 50\text{m}\Omega$	$\leq 50\text{m}\Omega$	$\leq 50\text{m}\Omega$
Insulation Resistance		$\geq 100\text{m}\Omega$	$\geq 100\text{m}\Omega$	$\geq 100\text{m}\Omega$	$\geq 100\text{m}\Omega$
Coil Voltage		110,230V AC	110,230V AC	110,230V AC	230V AC 85%~110%
Life	Electrical	10 $\bar{t}$ imes	10 $\bar{t}$ imes	10 $\bar{t}$ imes	10 $\bar{t}$ imes
	Mechanical	10 $\bar{t}$ imes	10 $\bar{t}$ imes	10 $\bar{t}$ imes	10 $\bar{t}$ imes
Operating Temperature		-40°C+55°C	-10°C+55°C	-40°C+55°C	-20°C+55°C
Dimensions(mm)					
					
Storage Battery (Working Reserve)		Time 150h	Time 70h	—	Rated Voltage: AC200V 50Hz 85%~110% Contact Form:1NC/1NO Accuracy : $\leq 2\text{s/day}(25^\circ\text{C})$ Expectancy Display:LCD Mounting Form: From panel,DIN Rail
Minimum Setting Unit		30Minutes	15Minutes	0.5Minutes	Programmable: 8time week or day Memory Backup:15days
Set up Times		30m/per times 48 times	15m/per times 96 times	1M,1.5M,2M,2.5M 3M,3.5M,4.5M,5M 5.5M,6M,6.5M,7M	